

## 8-Port Full Gigabit Managed POE Switch with 2 SFP Slots

MODEL: SN8200-8P-2FM



### Introduction

SN8200-8P-2FM is a fully Gigabit two layer network management switch designed and developed solely for the purpose of building high-performance gigabit network requirements. 8 full Gigabit RJ45 ports and 2 separate Gigabit SFP (Mini GBIC), Provide a comprehensive security protection system, Perfect QoS strategy and rich VLAN function, Management and maintenance are simple and can be applied to small and medium enterprises, Core layer of community and school.

#### Full gigabit access

Provides 8 10/100/1000M adaptive RJ45 port, all the ports have the line speed forwarding capacity; provide 2 independent Gigabit SFP (Mini GBIC) expansion slot optical fiber module, fully protect user investment, convenient and flexible.

#### Comprehensive safety protection system

Simple operation, simplifying the management of network; combination of ARP attack protection function, completely solve the network ARP spoofing attacks; support port security, can limit the number of port MAC address, MAC address effective defense attack; support DoS attack protection, effectively guarantee the network security.

#### Powerful VLAN capabilities

IEEE, 802.1Q, VLAN, meet the needs of different users, make the network more convenient, efficient and safe.

#### Rich QoS strategy

3 priority modes based on port, IEEE802.1p and DSCP to guarantee the priority processing of key business data; support traffic control function, and can reasonably allocate bandwidth.

**Multilevel access control policy**

Powerful hardware ACL capacity, support L2~L4 data stream classification; easy network monitoring, traffic regulation, priority weight markers and data forwarding control; support time based ACL control, easy to realize the time accurate access control needs; support port and MAC 802.1x based authentication based on user access, easy setup.

**Reliability design**

STP/RSTP/MSTP two layer link protection technology, greatly improve the ability of fault tolerance, redundancy link, to ensure stable operation of the network; provide static convergence and dynamic aggregation of two kinds of convergence pattern, effectively increase the link bandwidth, improve link reliability, while achieving load balancing, link backup; support multicast management, through the IGMP Snooping technology, effective inhibition of multicast overload caused by network congestion.

**Secure network management and maintenance**

CLI command line (Console, Telnet), Web network, SNMP (V1/V2c/V3, SSH (V1/V2) and other management methods, to achieve fast and convenient network management; support user identity classification, filtering and other functions, enhanced security configuration; support port data monitoring, real-time monitoring of network status, to easily achieve the global unified management of the network, convenient flexible.

**Advanced watchdog Technology**

System integration against false halt system, when the system resources exhausted or the system suspended tasks and other unexpected circumstances, the system will automatically restart, to ensure reliable operation of the network.

**Excellent PoE power supply performance**

PoE features comply with IEEE, 802.3af and IEEE 802.3at standards, automatically detect and identify equipment in accordance with IEEE, 802.3af and IEEE 802.3at standards, and supply power to them;

Intelligent power supply management, flexible power supply scheduling, conditions restart, conditional shutdown, adapt to complex office environment applications;

POE police function, real-time automatic device on-line detection function, when the lower equipment crashes, automatically restart the port power supply, to ensure rapid restoration of the network, without manual operation.

**Specifications**

Hardware	
Model	SN8200-8P-2FM
Port	8*10/100/1000M
	2GE SFP
Management port	1*Console
Layer	Layer 2 OSI Model
LED indicator	All ports LED indicator link, PoE, SFP status
Reset KEY	1
Switching capacity	20Gbps
Packet forwarding	14.44Mpps
POE port	8
POE standards	IEEE802.3af/at max 30W/port
CPU	500MHZ
RAM	128M
MAC	8K
buffer	4.1M
FLASH	16M
transmission	Store and forward
Environmental	working temperature : 0°C~50°C
	Storage temperature : -40°C~70°C
	Operating humidity : 10%~90% Non-coagulation
	Storage humidity : 5%~95% Non-coagulation
Product size	210(L)*140(W)*45(H)mm
Packing size	260(L)*205(W)*67(H)mm
Weight	1.8kg
Power in	AC 100~240V 50~60Hz
Power	120-150W

WEB software function	
standards	IEEE 802.3x IEEE 802.3, IEEE 802.3u, IEEE 802.3ab, IEEE 802.3z IEEE 802.3ad IEEE 802.3q, IEEE 802.3q/p IEEE 802.1w, IEEE 802.1d, IEEE 802.1S
MAC Address	8K MAC addresses; MAC address learning and aging
VLAN	4k VLANS; Port-based VLANs; 802.1Q VLAN
Spanning Tree	STP(Spanning Tree Protocol) RSTP/MSTP( Rapid Spanning Tree Protocol) EPPS ring network protocol EAPS ring network protocol 802.1x argumentation agreement
Link Aggregation	Max 8 aggregation groups, each supports 8 ports Static aggregation and dynamic aggregation
Port Mirror	Many-to-one port mirroring
Loop Guard	Loop protection function, real-time detection, rapid alarm, accurate positioning, intelligent blocking, automatic recovery
isolation	Support downlink ports isolated from each other and communicate with upstream port
Port flow control	Half duplex based back pressure control Full duplex based on PAUSE frames
line rate	Support port based input / output bandwidth management
IGMP Snooping	IGMPv1/2/3 and MLDv1/2 Snooping GMRP protocol registration Multicast address management, multicast VLAN, multicast routing ports, static multicast addresses
DHCP	DHCP Snooping
Storm suppression	Unknown unicast, multicast, unknown multicast, storm suppression of broadcast type Storm suppression based on bandwidth tuning and storm filtering
Security	User port+IP address+MAC ACL based on IP and MAC Security properties of port based MAC address quantities
QOS	802.1p port queue priority algorithm Cos/Tos, QOS sign WRR (Weighted Round Robin), Weighted priority rotation algorithm



## L2-Managed PoE Switch

## DATASHEET

	WRR, SP, WFQ, 3 priority scheduling models
Port	Auto-MDIX ; Auto negotiation
system maintenance	Upgrade package upload; system log view WEB restore factory configuration
PoE Management	Open or close port Standard POE scheduling management A variety of timing reset function (recently upgraded) POE Automatic equipment on-line inspection
Management and maintenance	WEB Browser Remote configuration and maintenance using Telnet SNMP V1/V2/V3; SSH V1/V2 RMON